

Wireless Precision Temperature Sensor (DLTi-probe)

DLTi-probe



- Accurate wireless temperature measurement
- Battery life of over 6 years
- Compatible with all Wireless Value Base Stations
- Signal range of 1,600 metres (line of sight)

Wireless Precision Temperature Sensor (DLTi-probe)

DLTi-probe



Description

DLTi-probe

The Wireless Value DLTi-probe measures temperature. Thanks to its detachable probe, the sensor housing can stay in place during calibration work, because the calibration values are stored in the probe itself. Measurement results are transmitted wirelessly to the base station, where the data can be used for monitoring and analysis.

- Memory for storing 10,000 measurements
- Adjustable measurement interval
- Robust IP54 ABS housing
- Suitable for wall mounting
- Existing system can easily be extended with additional sensors
- User-replaceable battery
- Unique network ID to prevent interference with other wireless systems

Wireless Precision Temperature Sensor (DLTi-probe)

DLTi-probe

Specifications

General

Battery type	AA
Battery life	Over 6 years

Measurement range

Temperature	-20 °C to +80 °C
Operating limits	-20 °C to +80 °C
Signal range	1,600 metres, line of sight

Measurement accuracy

Temperature	± 0.3 °C from -20 °C to 80 °C
-------------	-------------------------------

Measurement resolution

Temperature	0.1
-------------	-----

Legislation and standards

RED (Radio Equipment Directive)	yes
CE	yes
EN 300 220	yes

Technical specifications

Battery voltage	3.6
IP rating	IP54

Dimensions

Housing dimensions	105 (l) x 70 (w) x 34 (h) mm
--------------------	------------------------------